

## DATA SHEET

## **CI873A** ABB Ability™ System 800xA® hardware selector



The CI873A is an AC 800M communication interface that connects to external Ethernet devices using the EtherNet/IP protocol. The TP867 Baseplate has two RJ45 Ethernet connectors, but only the CH1 connector that supports 100Mbps is used. The CI873 expansion unit contains the CEX-Bus logic, a communication unit, and a DC/DC converter that supplies the required voltage from +24 V supply through the CEX-Bus.

The CI873A module will only work with System 800xA 6.0.3.3, 6.1.1 and subsequent versions. The CI873A support 6 redundant pairs of CI873A from 5.1 FP4.

## Features and benefits

- Supports Ethernet/IP and Device Net protocols
- Support 6 redundant pairs of CI873A from 5.1 FP4

| General info                     |                         |  |
|----------------------------------|-------------------------|--|
| Article number                   | 3BSE092695R1            |  |
| Communication protocol           | EtherNet IP / DeviceNet |  |
| Master or slave                  | Master                  |  |
| Transmission speed               | 10/100 Mbit/s           |  |
| Line redundancy                  | No                      |  |
| Module redundancy                | Yes                     |  |
| Hot Swap                         | Yes                     |  |
| Used together with HI Controller | Yes                     |  |

| Detailed data         |                      |  |
|-----------------------|----------------------|--|
| Max units on CEX bus  | 12                   |  |
| Connector             | RJ-45 female (8-pin) |  |
| 24 V consumption typ. | typ 160 mA           |  |

| Environment and certification |  |  |
|-------------------------------|--|--|
| Temperature, Operating        | +5 to +55 °C (+41 to +131 °F)                                      |  |
| Temperature, Storage          | -40 to +70 °C (-40 to +158 °F)                                     |  |
| Altitude                      | 2000 m according to IEC/EN 61131-2                                 |  |
| Pollution degree              | Degree 2 according to IEC/EN 61131-2                               |  |
| Corrosion protection          | G3 compliant to ISA 71.04  |  |
| Relative humidity             | 5 to 95 %, non-condensing  |  |
| Protection class              | IP20 according to EN60529, IEC 529                                 |  |
| CE-marking                    | Yes  |  |
| Electrical Safety             | UL 61010-1, UL 61010-2-201   |  |
| Hazardous location            | UL 60079-15, cULus Class 1, Zone 2, AEx nA IIC T4, ExnA IIC T4Gc X |  |
| Marine certificates           | DNV-GL, (Pending: ABS, BV, LR)                                     |  |
| RoHS compliance               | DIRECTIVE/2011/65/EU (EN 50581:2012)                               |  |
| WEEE compliance               | DIRECTIVE/2012/19/EU   |  |

| Dimensions              |                    |  |
|-------------------------|--------------------|--|
| Width                   | 59 mm (2.3 in.)    |  |
| Height                  | 185 mm (7.3 in.)   |  |
| Depth                   | 127.5 mm (5.0 in.) |  |
| Weight (including base) | 700 g (1.5 lbs)    |  |



solutions.abb/800xA solutions.abb/controlsystems

## \_

800xA and Symphony Plus is a registered trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document. We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2024 ABB All rights reserved